

ISOLATED DC-DC CONVERTERS



MODEL NUMBER	INPUT RANGE	OUTPUT	POWER
WA2412300	18V-32V		
WA4812300	29V-60V	13.8V (I max. 22A)	300 Watt Size 115x72x49mm
WA8012300	50V-100V		
WA4824300	29V-60V	26.0V (I max 11.5A)	
WA8024300	50V-100V		
WA4812450	29V-60V		450 Watt Size 120x72x54mm
WA8012450	50V-100V	13.8V (I max. 33A)	
WA9612450	62V-142V		
WA14412450	80V-175V		
WA4824450	29V-60V		
WA8024450	50V-100V	26.0V (I max. 17A)	
WA9624450	62V-142V		
WA14424450	80V-175V		
WA4812900	29V-60V		900 Watt Size 147x90x58,5mm
WA8012900	50V-100V	13.8V (I max. 60A)	
WA9612900	62V-142V		
WA4824900	29V-60V		
WA8024900	50V-100V	26.0V (I max. 32A)	
WA9624900	62V-142V		
WA48121500	29-60V	13.8V (I Max. 105A)	1500 Watt Size 165x104x62mm
WA96121500	60-150V		
WA96241500	60-150V	26V (I Max. 56A)	
WA80281500	40-100V	28V (I Max. 52A)	

FEATURES

- Isolated Switching Regulator
- Output power max. 300W/450W/900W/1500W
- Compact design
- Encapsulated IP65
- On / Off Key switch input
- Vibration resistant
- Wide input range
- Short circuit protection
- Contact cooling
- Connector Molex Mini-Fit Sr.
- Over temperature protected